



Meets or exceeds all ACT® Standards

*ACT® Registered Certification Marks

Content	25% Rayon 24% Polyester 21% Post Consumer Recycled Polyester 20% Nylon 10% Post Industrial Recycled Polyester
Finish	Soil and Stain Repellent
Backing	Acrylic
Weight	16.0 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 77 per inch Picks: 178 per inch
Repeat	H - 13.75 " V - 18.0"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Abrasion Resistance	ASTM D4157	60,000 double rubs*
Brush Pill	BRUSH + SPONGE	3
Tensile Strength	ASTM D5034	Warp: 205.0 lbs. Fill: 204.0 lbs.
Tear Strength	ASTM D2261	Warp: 57.0 lbs. Fill: 39.0 lbs.
Seam Slippage	ASTM D4034	Warp: 62.0 lbs. Fill: 89.0 lbs.
Colorfastness to Crocking	AATCC 8	Dry: 4.0 Wet: 4.0
Colorfastness to Light	AATCC 16	Hours: 40.0 Class: 4.0

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

High Performance	Yes
------------------	-----

Please refer to Detailed Cleaning Instructions.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

1-800-841-8111

Visit us at BurchFabrics.com