# Burch



Repeats Not Shown to Scale

## Nimbus Smoke 1009674

Meets or exceeds all ACT® Standards

Made in the USA High Performance Fabric Soil and Stain Repellent



\*ACT® Registered Certification Marks

#### **Fabric Specifications**

Content	25% Rayon 24% Polyester 21% Post Consumer Recycled Polyester 20% Nylon 10% Post Industrial Recycled Polyester
Finish	Soil and Stain Repellent
Backing	Acrylic
Weight	16.0 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 77 per inch Picks: 178 per inch
Repeat	H - 13.75 " V - 18.0"
Directional	Yes
Railroaded	No
Made in the USA	Yes

#### Performance Characteristics

Abrasion Resistance ASTM D4157	60,000 double rubs*	
Brush Pill Brush + sponge	3	
Tensile Strength ASTM D5034	Warp: 205.0 lbs. Fill: 204.0 lbs.	
Tear Strength ASTM D2261	Warp: 57.0 lbs. Fill: 39.0 lbs.	
Seam Slippage ASTM D4034	Warp: 62.0 lbs. Fill: 89.0 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

### **Additional Attributes**

High Performance	Yes		
Recommended Cleaning			
Please refer to Detailed Cleaning Instructions.			

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{thm:condition} Final \ determination \ of \ the \ suitability \ of \ this \ product \ for \ an \ application \ rests \ with \ the \ user.$ 

<sup>\*</sup> Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

<sup>\*\*</sup> This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.