Burch



Repeats Not Shown to Scale

Academy Shadow 1012017

Meets or exceeds all ACT® Standards

PVC Free Polyurethane
Ink Cleanable
Denim Dye Cleanable
Bleach Cleanable
FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% PVC Free Polyurethane
Backing	100% Polyester
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	25.4 oz. per linear yd
Thickness	1.40 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No

Additional Attributes

Denim Dye Cleanable PFAS Free PVC Free Prop 65 Compliant 16P Phthalate Free Free of Added FR Chemicals / CAL AB2998 Compliant Yes BPA Free Free of Conflict Minerals Yes
PVC Free Yes Prop 65 Compliant Yes 16P Phthalate Free Yes Free of Added FR Chemicals / CAL AB2998 Compliant Yes BPA Free Yes
Prop 65 Compliant Yes 16P Phthalate Free Yes Free of Added FR Chemicals / CAL AB2998 Compliant Yes BPA Free Yes
16P Phthalate Free Yes Free of Added FR Chemicals / CAL AB2998 Compliant Yes BPA Free Yes
Free of Added FR Chemicals / CAL AB2998 Compliant Yes BPA Free Yes
BPA Free Yes
3.77.00
Free of Conflict Minerals Yes
Formaldehyde Free Yes
Free of Heavy Metals Yes
Lead Free Yes
Sulfide Stain Resistant Yes
TRIS Free Yes
HPD on File Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 double rubs*
Tensile Strength ASTM D751-06	Warp: 127.0 lbs. Fill: 232.0 lbs.
Tear Strength ASTM D751-06	Warp: 9.3 lbs. Fill: 12.2 lbs.
Seam Slippage ASTM D751-06	Warp: 83.0 lbs. Fill: 80.9 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
UV Resistance AATCC 16	200 hours
Adhesion astm d751-06	Warp: 4.6 lbs. Fill: 4.6 lbs.
Blocking cffA-4	1
Cold Crack CFFA-6	-20° F
Flex ASTM D2097	25,000 cycles
Hydrolysis	10 Weeks
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

The use of polyurethane for welt cord in upholstery applications is strongly discouraged. Even though Burch's polyurethane products are designed to exceed industry abrasion standards, when used with welt cord the exposed material becomes more vulnerable to abrasion and may experience premature de-lamination. Burch cannot be held responsible for damage that may occur when used in a welt cord application.

Final determination of the suitability of this product for an application rests with the user.

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommended Cleaning	
Please refer to Detailed Cleaning Instructions.	

Toll Free **1.800.841.8111**

Visit us at BurchFabrics.com